



Gas spring G 6-15

Extension force F1	40 - 400 Newton
Progression	22 %
Piston rod	Ø 6 mm steel chromium plated
Cylinder	Ø 15 mm steel black spray coated
Fittings	Steel zinc plated

GZ 07

AU 16
(available on both ends)

AS 20

AR 16

AG 27

GA 20

GZ 07

AB 09
only possible on cylinder end

PF 22

WG 22

WX 22

<p>Standard Strokes [mm]</p> <p>20, 30, 40, 50, 60, 70, 80, 100, 110, 120, 140, 150, 160, 170, 180, 190, 200, 220, 250, 300</p> <p>*Special strokes available upon request</p>	<p>Stroke</p>
<p>Base Length L</p> <p>= 2 x Stroke + 55mm</p>	<p>L (±2)</p>
<p>Overall Extended Length</p> <p>= L + L1 + L2</p>	<p>L1</p> <p>L2</p>
<p>Extras</p> <p>Codes 4, 5, 6, 7, VV (see pages 4 & 28)</p>	
<p>Gas Spring and fittings</p> <p>also available in complete stainless steel (VV)</p>	
<p>For additional end fittings and also mounting brackets</p> <p>see pages 29 and 30</p>	
<p>Order Code example</p> <p>G06 15 0050 1 0180 AU16 AB09 100N (see page 4)</p>	